



The Titan Snapshot






TITAN (FLAT TOP) CONCRETE SHELTERS

LAST UPDATED 2/22/2024

MODEL TYPE	DIMENSIONS	CAPACITY	PRICE
5 x 7 Flat Top	5' x 7' x 6'2" tall	6 person	\$4,500
5 x 7 Decorative			\$5,300
Jumbo Flat Top	6'8" x 10' x 6'2" tall	16 person	\$7,400
Jumbo Decorative			\$8,200
			Financing Available

FEATURES OF THE TITAN CONCRETE SHELTERS

- **Ventilation:** 6" vent and 8" wind turbine vent
- **Steps / Ladder:** 6 skid-resistant steps with double safety handrails
- **Door:**
 - Reinforced steel door and frame meet FEMA 320 and 361 standards and ICC 500 standard
 - The door has a gas spring assist for easy opening
 - The door has a 3-point locking system for max security
- **Color:** Optional decorative finishes are available for all Titan models in gray rock or brown rock finish for additional cost
- 10-year manufacturer warranty
- Made in Oklahoma

STRUCTURAL SPECIFICATIONS	INSTALLATION REQUIREMENTS	TESTING SPECIFICATIONS	
<ul style="list-style-type: none"> • Average weight of 14,000 pounds • Min. of 6,000 psi concrete walls and floor reinforced with reinforced steel rebar • Shelter walls over 4 in. thick • 2 piece unit with sealer between parts • Once installed top of shelter will be flush or approx. 6" above the ground 	<ul style="list-style-type: none"> • Requires 10 ft. horizontal clearance (or more if sharp turns are required) and 14 feet vertical clearance • Approx. 2 hour installation • Storm shelter appearance can be enhanced with landscape timbers, rail road ties, and/or stone 	<ul style="list-style-type: none"> • Designed in accordance of FEMA 320 and 361 and ICC 500 standards • Door has been tested at Texas Tech Wind and Science Institute 	     <p>Examples of available decorative finishes</p>

Survivor Shelters
17311 Ok-66
Claremore, OK 74017

Give Survivor Shelters a call to find the right shelter for you!

918-341-4672

www.survivorsheltersllc.com