

LifeSaver Series Snapshot

LIFESAVER & LIFESAVER Mini CONCRETE SHELTERS

LAST UPDATED 2/22/2024

MODEL TYPE

LifeSaver Decorative LifeSaver LifeSaver Mini

DIMENSIONS

 $5' \times 7' \times 5'9" \text{ tall}$

5' x 4'6" x 5'9" tall

CAPACITY

12 person

6 person

PRICE

\$4,350

\$4,850

\$3,600

Financing Available

FEATURES OF LIFESAVER & LIFESAVER Mini CONCRETE SHELTERS

- **Ventilation:** 6" vent and 6" wind turbine vent
- Steps / Ladder: Easy access concrete molded steps with safety handrail
- Door:
 - Reinforced steel door and frame meet FEMA 320 and 361 standards and ICC 500 standard
 - The door has a gas spring assist for easy opening
 - The door has a 3-point locking system for max security
- Color: Optional decorative finishes are available for the full-size LifeSaver model in gray stone or brown rock finish for additional cost
- 10-year manufacturer warranty
- Made in Oklahoma

STRUCTURAL SPECIFICATIONS

- Average weight of 14,000 pounds
- Min. of 6,000 psi concrete walls and floor reinforced with heavy steel rebar welded "cage"
- Shelter walls over 4 in. thick
- 2 piece unit with waterproof sealer between parts
- Once installed top of shelter is 2 to 3 feet above ground

INSTALLATION REQUIREMENTS

- · Requires 10 ft. horizontal clearance (or more if sharp turns are required) and 14 feet vertical clearance
- Approx. 2 hour installation
- Storm shelter appearance can be enhanced with landscape timbers, rail road ties, and/or stone

TESTING SPECIFICATIONS

- Designed in accordance of FFMA 320 and 361 and ICC 500 standards
- Door has been tested at Texas Tech Wind and Science Institute







Examples of available decorative



finishes

Survivor Shelters

17311 Ok-66 Claremore, OK 74017 Give Survivor Shelters a call to find the right shelter for you!

918-341-4672 www.survivorsheltersllc.com